

# ADAM-6015 ADAM-6017 ADAM-6018+

7-ch Isolated RTD Input Modbus TCP Module  
8-ch Isolated Analog Input Modbus TCP Module  
with 2-ch DO

8-ch Isolated Thermocouple Input Module



ADAM-6015



ADAM-6017



ADAM-6018+



## Specifications

### Analog Input

- **Channels** 7 (differential)
- **Input Impedance** > 10 MΩ
- **Input Connections** 2 or 3 wire
- **Input Type** Pt, Balco and Ni RTD
- **RTD Types and Temperature Ranges**
  - Pt 100 -50°C ~ 150°C
  - 0°C ~ 100°C
  - 0°C ~ 200°C
  - 0°C ~ 400°C
  - 200°C ~ 200°C
  - Pt 1000 -40°C ~ 160°C

Supports both IEC 60751 ITS90 (0.0385 W/W/°C) and JIS C 1604 (0.0392 W/W/°C)

  - Balco 500 -30°C ~ 120°C
  - Ni 518 -80°C ~ 100°C
  - 0°C ~ 100°C
- **Accuracy** ±0.1% or better
- **High speed mode** ±0.5% or better
- **Span Drift** ±25 ppm/°C
- **Zero Drift** ±6 μV/°C
- **Resolution** 16-bit
- **Sampling Rate**
  - 10 sample/ second (total)
  - High speed mode: 1K sample/second (total)
  - CMR @ 50/60 HZ 90dB
  - NMR @ 50/60 HZ 60dB
  - \* high speed mode does not support CMR/ NMR
- **Wire Burnout Detection**

## Ordering Information

- **ADAM-6015** 7-ch Isolated RTD Input Modbus TCP Module

## Specifications

### Analog Input

- **Channels** 8 (differential)
- **Input Impedance** > 10 MΩ (voltage)  
120 Ω (current)
- **Input Type** mV, V, mA
- **Input Range**
  - ±150mV, ±500mV, ±1 V, ±5V, ±10V, 0 ~ 150mV, 0 ~ 500mV, 0 ~ 1V, 0 ~ 5V, 0 ~ 10V, 0 ~ 20mA, 4 ~ 20mA, ±20mA
- **Accuracy**
  - ±0.1% (voltage)
  - ±0.2% (current)
- **Span Drift** ±25 ppm/°C
- **Zero Drift** ±6 μV/°C
- **Resolution** 16-bit
- **Sampling Rate** 10 or 100 sample/ second (total)  
CMR @ 50/60 HZ 90dB  
NMR @ 50/60 HZ 67dB
- **Common-Mode Voltage** 350V<sub>DC</sub>

### Digital Output

- **Channels** 2, open collector to 30 V, 100 mA max. load
- **Power Dissipation** 300 mW for each module
- **Output Delay** On: 100μs  
Off: 150μs

## Ordering Information

- **ADAM-6017** 8-ch Isolated AI with 2-ch DO Modbus TCP Module

## Specifications

### Analog Input

- **Channels** 8 (differential)
- **Input Type** Thermocouple
- **Thermocouple Type and Range:**

<b>J</b>	0 ~ 760°C	<b>R</b>	500 ~ 1,750°C
<b>K</b>	0 ~ 1,370°C	<b>S</b>	500 ~ 1,750°C
<b>T</b>	-100 ~ 400°C	<b>B</b>	500 ~ 1,800°C
<b>E</b>	0 ~ 1,000°C		
- **Accuracy@25°C** Type J,K,E,R,S: ±0.1% FSR Max  
Type B: ±0.15% FSR Max  
Type T: ±0.2% FSR Max
- **Span Drift** ±25 ppm/°C
- **Zero Drift** ±6 μV/°C
- **Resolution** 16-bit
- **Sampling Rate** 10 sample/ second (total)
- **Wire Burnout Detection**

## Ordering Information

- **ADAM-6018+** 8-ch Isolated Thermocouple Input Module

## Common Specifications

### General

- **Certification** CE, FCC, UL
- **LAN** 10/100Base-T(X)
- **Power Consumption** 2.5 W @ 24 V<sub>DC</sub> (ADAM-6015)  
2.7 W @ 24 V<sub>DC</sub> (ADAM-6017)  
1 W @ 24 V<sub>DC</sub> (ADAM-6018+)
- **Connectors** 1 x RJ-45 (LAN), Plug-in screw terminal block (I/O and power)

- **Watchdog** System (1.6 second) and Communication (programmable)  
10 ~ 30 V<sub>DC</sub>
- **Power Input**
- **Supports Peer-to-Peer**
- **Supports GCL**
- **Supports Modbus/TCP, TCP/IP, UDP, RESTful, MQTT (D version), SNMP (D version) Protocols**
- **Protection**
  - **Isolation Protection** 2,000 V<sub>DC</sub>
  - **Built-in TVS/ESD Protection**
  - **Power Reversal Protection**

### Environment

- **Operating Temperature** -10 ~ 70°C (14 ~ 158°F)  
-40 ~ 70°C (-40 ~ 158°F) (D version)
- **Storage Temperature** -20 ~ 80°C (-4 ~ 176°F)  
-40 ~ 85°C (-40 ~ 185°F) (D version)
- **Operating Humidity** 20 ~ 95% RH (non-condensing)
- **Storage Humidity** 0 ~ 95% RH (non-condensing)