



KEY FEATURES

- Latest and Powerful Intel® Atom® x6000E Processor
- Fan-less and Rugged Design, Wide Temperature Operation (-40 °C to 70 °C)
- 6-36VDC Wide Range Power Inputs
- Most Flexible IOs and Expansion for Industrial Applications
- Intel® TCC and TSN Support for Real-Time Computing
- DIN Rail or Wall Mount Options

SPECIFICATIONS

System Core

Processor	Intel® Atom® x6000E Processor -iEP-5000G (x6425RE, 12W) -iEP-5001G (x6212RE, 6W)
Video	1 x HDMI 2.0b, 1 x VGA
Memory	2 x DDR4 3200MHz SO-DIMM, up to 32GB (In-Band ECC)

I/O Interface

Ethernet	3 x 1GbE
PoE (Option)	2x Intel I210AT ports, each port supports IEEE 802.3AF PoE
Serial Port	3 x RS-232/422/485
USB	2 x USB 3.2 Gen1x1 2 x USB 2.0
Digital I/O	4DI/4DOs
Audio	1 x Mic in 1 x Line out

Expansion

SIM	1 x Nano SIM Card slot
RF& Antenna (Option)	M.2 Wi-Fi 6E module supports IEEE 802.11 a/b/g/n/ac/ax + BT 5.2 3 x 4G LTE antenna + 2 x Wi-Fi antenna 4 x 5G antenna + 2 x Wi-Fi antenna
M.2 Socket	1 x M.2 (Key B, 3042/3052) -For PCIe Gen3 x1 and USB3.2 Gen1x1 5G/4G LTE module 1 x M.2 (Key E, 2230) -For CNVI/PCIe Gen3 x1 and USB 2.0 Wi-Fi/BT module

Manageability / Security

Manageability	WDT, Intel® In-Band Manageability
Security	TPM2.0

Power Supply

DC Input	Basic SKU : 6-36VDC, 80V Surge Protection PoE SKU : 19-36VDC, 80V Surge Protection Supports Latch Adaptor
AC to DC Adaptor (Option)	AC input 100-240Vac, 1.5A 50-60Hz, DC output 19V, 3.42A, 65W Adaptor (Latch type) for iEP-5000G-000 only.

Storage Device

SD Slot	1 x Micro SD card slot(SD Card specification version 3.01)
SATA(Optional)	1 x 2.5" 9.5mm SATA3 SSD
M.2 Socket	1 x M.2 Key M Socket (2280) with PCIe Gen3 x2/SATA3 for Storage

Mechanical

Dimensions	58mm (W) x 125mm (D) x 157mm (H)
Indicator	1 x SATA / NVMe Storage LED, 1 x Wi-Fi / BT LED
Function	Power on Button with LED, Clear CMOS Button
Net Weight	1.3kg
Mounting	DIN-Rail or Wall mounting

Environmental

Operating Temperature	For Basic SKU : -40°C ~ 70°C (-40°F~158°F) (w/ airflow 0.5~0.8m/s) For POE SKU : -40°C ~ 50°C (-40°F~158°F) (w/ airflow 0.5~0.8m/s)
Storage Temperature	-40°C ~ 85°C (-40°F~185°F)
Humidity	~95% @ 40°C (non-condensing)
Vibration	Operating: 5 Grms, 5-500 Hz, 3 axes with SSD
ESD	Contact +/-8 KV, Air +/-15 KV
Shock	Operating 50 G, half sine 11 ms duration with SSD
EMC	CE and FCC Class A (EN61000-6-4/-2)
Safety	LVD

Add-on Feature / OS Support

Real-Time Enablement	TSN, TCC support under YOCTO
OS Support	Windows 10, Linux

Order Information	Basic SKU		PoE SKU
	iEP-5000G-000	iEP-5000G-010	iEP-5000G-011
CPU	x6425RE	x6425RE	x6425RE
DC-IN Connector	Jack Type	Phoenix Type	Phoenix Type
2.5" Storage	Build to Order	Build to Order	N/A
Wifi/BT	Support**	Support*	Support*
4G LTE/5G	Support***	Support***	N/A
PoE	N/A	N/A	Default

*Support by additional Wifi/BT kit

**Support by additional 4G LTE/5G kit