

Discover the Ideal Digi Connect EZ Model to Meet Your Needs!



THE NEXT GENERATION OF SECURE SERIAL CONNECTIVITY

Explore a versatile range of 1 to 32 serial port connections, offering convenient access to vital equipment and machinery responsible for executing critical operations. The **Digi Connect EZ®** product family is tailored to fulfill the essential deployment requirements of industrial and logistics applications, retail and hospitality applications, and telecom and communications deployments.

KEY FEATURES INCLUDE:

- Click-to-connect technology that boots in seconds, configures in minutes, and runs for years
- Built-in **Digi TrustFence®** for device security, secure encrypted connections, and ongoing monitoring and support
- Easy setup and mass configuration with **Digi Navigator™** and **Digi Remote Manager®**
- Enhanced Service and Support Included — **Digi Lifecycle Assurance**

NOW INCLUDING



Digi Connect® EZ Mini



Digi Connect® EZ 2



Digi Connect® EZ 4



Digi Connect® EZ 4i

SPECIFICATIONS	EZ01-MA00-GLB	EZ02-CA00-GLB/ EZ02-CAG4-GLB	EZ04-WA00-GLB/ EZ04-WAG4-GLB	EZ04-IA00-EXT/ EZ04-IG4-EXT
Number of Ports	1	2	4	4
RS-232	✓	✓	✓	✓
RS-232/422/485	✓	✓	✓	✓
Ethernet	(1) RJ-45 10/100/1000	(1) RJ-45 10/100/1000	(1) RJ-45 10/100/1000	(1) RJ-45 10/100/1000
Power	9 – 30 VDC	9 – 30 VDC	9 – 30 VDC	9 – 30 VDC
RealPort® Connectivity	✓	✓	✓	✓
Cellular Support		✓	✓	✓
Central Management	Cloud	Cloud	Cloud	Cloud
Digi CORE® LTE Module		✓	✓	✓
Wi-Fi Client/Access Point			✓	✓

Discover the Ideal Digi Connect EZ Model to Meet Your Needs!



Digi Connect® EZ 8



Digi Connect® EZ 16



Digi Connect® EZ 32

SPECIFICATIONS	EZ08-A100	EZ08-B100	EZ08-C100	EZ08-D100	EZ08-E100	EZ16-A100/A200	EZ16-C100/C200	EZ32-A100/A200	EZ32-C100/C200
Number of Ports	8	8	8	8	8	16	16	32	32
RS-232	✓	✓		✓	✓	✓		✓	
RS-232/422/485			✓				✓		✓
Ethernet	(2) 10/100/1000	(2) 10/100/1000	(2) 10/100/1000	(2) 10/100/1000	(6) 10/100/1000	(2) 10/100/1000	(2) 10/100/1000	(2) 10/100/1000	(2) 10/100/1000
SFP+	2	2	2	2	2	2	2	2	2
Power	110-240 VAC/12 VDC	110-240 VAC/12 VDC	110-240 VAC/12 VDC	110-240 VAC/12 VDC	110-240 VAC/12 VDC	Field replaceable 110-240 VAC power (A200 is dual AC)	Field replaceable 110-240 VAC power (A200 is dual AC)	Field replaceable 110-240 VAC power (A200 is dual AC)	Field replaceable 110-240 VAC power (A200 is dual AC)
RealPort® Connectivity	✓	✓	✓	✓	✓	✓	✓	✓	✓
Cellular Support	✓	✓	✓	✓	✓	✓	✓	✓	✓
USB 3.0 Type A Ports	2	2	2	2	2	2	2	2	2
Central Management	Cloud	Cloud	Cloud	Cloud	Cloud	Cloud	Cloud	Cloud	Cloud
Digi CORE® LTE Module	✓	✓	✓	✓	✓	✓	✓	✓	✓
Wi-Fi Client/Access Point		✓							
Digital/Analog				2/1	2/1				

Explore our [Serial Connectivity solutions](#) →