

# GPU SuperServer SYS-521GU-TNXR

Universal 5U Dual Processor (Intel) GPU System with NVIDIA HGX™ H100 4-GPU SXM5 board, NVLINK™ GPU-GPU Interconnect, and Redundant 3000W Titanium Level Power Supplies



More details here

## Key Applications

High Performance Computing, AI/Deep Learning Training,

## Key Features

- 32 DIMM slots Up to 8TB: 32x 256 GB DRAM Memory Type: 4800MHz ECC DDR5;
- 10 PCIe Gen 5.0 X16 LP Slots;
- AIOM/OCP 3.0 Support; AIOM / OCP 3.0 Support; Flexible networking options;
- 2 M.2 NVMe and SATA for boot drive only; 10x 2.5" Hot-swap NVMe/SATA/SAS drive bays;



<b>Form Factor</b>	5U Rackmount Enclosure: 449 x 222.5 x 833mm (17.67" x 8.75" x 32.79") Package: 700 x 370 x 1260mm (27.55" x 14.57" x 49.6")
<b>Processor</b>	4th Gen Intel® Xeon® Scalable processors Dual Socket LGA-4677 (Socket E) supported  (Supports up to 350W TDP CPUs (Aircooled), Supports up to 350W TDP CPUs (Liquid Cooled))
<b>GPU</b>	Supported GPU: HGX H100 4-GPU SXM5 Multi-GPU Board CPU-GPU Interconnect: PCIe 5.0 x16 CPU-to-GPU Interconnect GPU-GPU Interconnect: NVIDIA® NVLink™
<b>System Memory</b>	32 DIMM slots Up to 8TB ECC LRDIMM, DDR5-4800MHz
<b>Drive Bays</b>	10x 2.5" hot-swap NVMe/SATA drive bays (10x 2.5" NVMe hybrid) 2 M.2 NVMe OR 2 M.2 SATA3
<b>Expansion Slots</b>	10 PCIe 5.0 X16 slot(s)
<b>On-Board Devices</b>	Chipset: Intel® C741 Network Connectivity: 2x 10GbE BaseT with Intel® X710-AT2 IPMI: Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
<b>Input / Output</b>	Video: 1 VGA port(s)



System Cooling	5 heavy duty fan(s) Liquid Cooling: Direct to Chip (D2C) Cold Plate (optional)
Power Supply	4x 3000W Redundant Power Supplies, Titanium Level Output Type: Backplanes (connector)
System BIOS	BIOS Type: AMI 32MB SPI Flash EEPROM
Management	SuperDoctor® 5; Watch Dog; NMI; SUM; KVM with dedicated LAN; SPM; Intel® Node Manager; SSM; IPMI 2.0; Redfish API; OOB Management Package (SFT-OOB-LIC )
PC Health Monitoring	CPU: Monitors for CPU Cores, Chipset Voltages, Memory 8+4 Phase-switching voltage regulator FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Height: 8.75" (222.5 mm) Width: 17.67" (449 mm) Depth: 32.79" (833 mm) Gross Weight: 225 lbs (102.1 kg) Net Weight: 166 lbs (75.3 kg) Packaging: 14.57" (H) x 27.55" (W) x 49.6" (D) Available Color: Black Front & Silver Body
Operating Environment	Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	<a href="#">Super X13DGU</a>
Chassis	CSE-458GTS-R3K06P