



SPC-1533-B1

15" Apollo Lake SoC Mobile Processor Fanless
Stainless Steel Chassis Touch Panel PC with Full
IP-66 & IP-69K

- > Intel® Apollo Lake SoC with Integrated Chipset
- > Projective Capacitive Touchscreen Full Flat Design
- > Waterproof Power Button
- > Rich and swappable I/O, 1 x LAN, 2 x USB, 1 x COM by M12 8-pin(male) with waterproof cover and chain
- > IP66 Air pressure relief valve
- > Metal Waterproof Connectors
- > Wide Range DC in +12V ~ +24V
- > Wide Temperature -10°C ~ 50°C
- > Full System IP66, IP69K
- > Multiple OS support (Win10, Linux, Android)
- > Optional WiFi/BT with waterproof antenna
- > Optional Auto Dimming/ High Brightness Solution

+ Spec

System Information

Processor	Intel® Celeron® Processor J3455
Platform Controller Hub	Intel Apollo Lake SoC integrated
System Memory	2 x 204-pin DDR3L 1866MTs SO-DIMM up to 16 GB
I/O Chipset	EC ITE IT8528E
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec./1sec.step
H/W Status Monitor	Monitoring SYSTEM Temperature and Voltage with Auto Throttling Control
TPM	Option for Infineon SLB9665 TPM 2.0
SBC	EMX-APLP

Expansion

Expansion	1 x M.2 (2230) A-Key support WiFi module
------------------	--

Storage

Storage	Default with 64GB mSATA
Other Storage Device	1 x 2.5" Drive Bay for SSD/HDD(by option)

Panel

LCD Size	15", 4:3
Display Type	XGA
Resolution	1024x768
Pixel pitch	0.297mm(H) x 0.297mm(V)
Luminance	300 cd/m ²
Contrast ratio	2000
Viewing angle	88 (U), 88 (D), 88(L), 88 (R)
Response time	16ms
Backlight	LED
Touch Type	Projective Capacitive
Touch Light Transmission	85%
Touch Controller	ILITEK COF Touch

I/O

USB Port	2 x M12 8-pin (male) for 2 x USB 2.0 with waterproof cover and chain
COM Port	1 x M12 8-pin (male) COM(RS-232/422/485) with waterproof cover and chain
SATA	1 x SATA III
Other	1 x WiFi with waterproof antenna (Optional)

Display

Graphic Chipset	Intel® HD Graphics 500
Spec. & Resolution	LVDS: Max. resolution 1920x1080 @ 60Hz eDP: Max. resolution 4096x2160 @ 60Hz

Audio

Audio Codec	Realtek ALC662 supports 2-CH
--------------------	------------------------------

Certifications

Certification Information	CE FCC Class A
----------------------------------	-------------------

Ethernet

LAN Chipset	2 x Intel I211AT Gigabit Ethernet
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	1 x M12 8-pin (male) for LAN with waterproof cover and chain

Power Requirement

DC Input	+12V ~ +24V
DC Input Connector	1 x M12 3-pin (male) for DC power with waterproof cover and chain

Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (24V @ 2.5A Adapter) AC-DC Adapter (Need waterproof M12/3Pin- D2.5DCJack-Plug 200cm cable for M12 DC in connector)
Mechanical & Environmental	
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F), by flow = 0.5
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Weight	5.7 Kgs
Vibration Test	With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Test	With CF/SSD : 10Grms, IEC 60068-2-27, Half Sine, 11ms
IP Rating	Whole System IP69K, IP66
Mounting Kit	Wall / Stand / VESA 75mm x 75mm, 100mm x 100mm
Power Mode	AT/ATX (ATX is default setting)
System Fan	Fanless
Construction - Front	Silver Stainless
Construction - Rear	Silver Stainless
Dimension	393 x 315.8 x 49 mm
Software Support	
OS Information	Win10 Linux Android x86 8.1
Ordering Information	
Ordering Information	SPC-1533-345-B1R intel Celeron J3455 F1-CPU/4GR/64GmSATA/LAN/4USB/COM/5M12(I/O,DC in)/Air Vent Valve/EMX-APLP ACC-ARM-D1R VESA STAND, 75mm & 100 mm ACC-ARM-D23R VESA STAND, 75mm & 100 mm