

PPC-415W

15.6" Fanless Widescreen Panel PC with Intel® 13th Gen Core™ i7/i5/i3 Processor



Features

- 15.6" true-flat Full HD LCD panel with projected capacitive touchscreen, anti-glare coating
- Intel® Core™ i7-1365URE/i5-1345URE/i3-1315URE processor with fanless system design
- Supports PCIe x4 or PCI expansion
- 1 x isolated RS-422/485 with auto flow
- Wide input power range (9 ~ 32 V_{DC})
- Dual 2500BASE-T Ethernet Supports Time-Sensitive Network(TSN) technology
- 3 x Independent displays
- 1 x M.2 bay (2242/2280) for storage only
- Support TPM2.0 hardware security
- Supports VESA 100 mounting interface



Introduction


Designed for high-performance computing 13th gen applications, PPC-415W with a 15.6" FHD provides a superior human-machine interface and reliability, with multi-touch screen, rich I/O and aluminum alloy front bezel. The inclusion of PCIe/PCI slot for fieldbus or proprietary card expansion increases the system's compatibility for diverse applications. In addition, Time Sensitive Network(TSN)configuration integrated allows more possibilities for optimized industrial applications

Specifications

	CPU	i7-1365URE	i5-1345URE	i3-1315URE	
System	Core	10	10	6	
	Frequency	1.70 GHz upto 4.9 GHz with Turbo	1.40 GHz upto 4.6 GHz with Turbo	1.20 GHz upto 4.5 GHz with Turbo	
	Cache	12 MB Intel® Smart Cache	12 MB Intel® Smart Cache	10 MB Intel® Smart Cache	
	Memory	2 x SODIMM, DDR5 4800, max. 32GB x 2			
	Storage	1 x 2.5" SATA bay (Max. 7mm) 1 x M.2 2242/2280 M Key slot for Storage (SATA or NVME PCIe x 4, support SATA RAID)			
	Network (LAN)	2 x Intel I226LM controller; Speed: 10M / 100M / 1000M / 2.5G			
	I/O	5 x Serial ports: 2 x RS-232, 1 x RS-422/485 with 1K VDC isolation, 2 x RS-232 (on right side optional) 3 x USB3.2, 1 x USB2.0 1 x Line-Out, 1 x Mic-In 1 x HDMI 1.4 1 x DisplayPort (1.4a) 1 x 8bit GPIO (optional)			
	Expansion	1 x M.2 2230 E Key slot for wireless card 1 x PCIe x 4 ; 1 x PCI (optional)			
	Watchdog Timer	255 timer levels, set up by software			
	Security	1 x TPM2.0			
	Speaker	2 x 1W			
	Physical Characteristics	Dimensions	419.7 x 269 x 59 mm (16.5 x 10.6 x 2.3 in)		
		Enclosure Front bezel	Die cast aluminum alloy Rear: PC+ABS		
Mounting		Panel / VESA (100)			
Weight		5.4kg (11.9 lb)			
OS Support	OS Support	Microsoft® Windows 11 (64-bit), Win 10 IOT LTSC, Linux			
Power Consumption	Input Voltage	9 ~ 32 V _{DC}			
	Power Consumption	i5-1345URE Typ.70W Max.105W (Burn-in test 8.1 in Windows 10 64bit)			
LCD	Display Type	15.6" TFT LCD (LED backlight)			
	Max. Resolution	1920 x 1080			
	Viewing Angle	85 (Left), 85 (Right), 85(Up), 85(Down)			
	Luminance (cd/m ²)	450			
	Contrast Ratio	800			
	Backlight Lifetime	50,000 hr (min.)			
Touchscreen	Touch Type	Multi-touch projected capacitive			
	Light Transmission	88 % ± 2 %			
	Controller	USB interface			
Environment	Operating Temperature	-20 ~ 60 °C (-4 ~ 140 °F)			
	Storage Temperature	-40 ~ 60 °C (-40 ~ 140 °F)			
	Relative Humidity	95% @ 40 °C (Non-Condensing)			
	Shock	Operating 10 G Peak Acceleration (11 ms Duration), Follows IEC 60068-2-27			
	Vibration	Operating Random Vibration Test 5 ~ 500Hz, 2Grms @with SSD, Follows IEC 60068-2-64			
	EMC	CE, FCC Class B, EN 61000-6-2, BSMI, UKCA			
	Safety	CB, UL, CCC, UKCA			
Front Panel Protection	IP66 compliant				

Dimensions

Unit: mm




Panel Cutout Dimensions: 413 x 262 mm (16.25 x 10.31 in)

Ordering Information

Part Number	Description
PPC-415W-PD3A	15.6" PPC w/Intel i3-1315URE, P-CAP
PPC-415W-PD5A	15.6" PPC w/Intel i5-1345URE, P-CAP
PPC-415W-PD7A	15.6" PPC w/Intel i7-1365URE, P-CAP
96PSA-A150W19P2-4	Power adapter 100-240V 150W 19V
1702002600	Power Cable UL/CSA (USA) 180D 125V10A 1.83M
1702002605	Power Cable 90D 220V EUROPEAN 250V/6A 1.8M
1700000237	Power Cord PSE 3P 12A 125V 183cm
96CB-POWER-B-1.8MA	Power code 3P CCC(China) 1.8M
PPC-174T-WL-MTE	Wall mount kit for PPC series
PPC-STAND-A1E	Stand for PPC series
PPC-ARM-A03	ARM VESA Standard for PPC series
PPC-WLAN-D2	M.2, WiFi6 +BT5.2, 2T2R, w/Antenna
98R3P321100	Additional ports module (either two RS-232 or one RS-232 and one GPIO port)
989KB01001E	PClex1 to PCI riser card

I/O View



- A. 1 x Expansion slot (PCIe x 4 or PCI)
- B. 3 x USB3.2, 1 x USB2.0
- C. 1 x Mic-In/Line-Out
- D. 2 x Intel Gigabit Ethernet
- E. 1 x HDMI
- F. 1 x DisplayPort
- G. 2 x RS-232
- H. 1 x Isolated RS-422/485
- I. 1 x DC inlet and AT/ATX switch
- J. 1 x Power button
- K. 2 x RS-232 (on right side optional)