

1) Tightening torque



Basic features

Approval/Conformity	CE cULus EAC WEEE
Chroma	Monochrome
Frame rate	max. 9.6 fps
Image resolution	12.4 MP (4112 x 3008 pixels)
Pixel size	3.45 x 3.45 µm
Sensor chip	Sony IMX304
Sensor type Vision	1.1" global shutter CMOS
Standards	IEEE 802.3af EMVA 1288 GigE Vision GenICam
Version	GigE Vision industrial camera

Electrical connection

Connection 1	GigE-Bus: M12x1-Female, 8-pin, X-coded
Connection 2	Power / IO: M12x1-Male, 12-pin, A-coded
Polarity reversal protected	yes
Short-circuit protection	yes

Electrical data

Current draw max.	500 mA
Operating voltage Ub	11...25 VDC PoE

Environmental conditions

Ambient temperature	0...45 °C
EN 60068-2-27, Shock	100 G, half-sine, 1000 pos., 1000 neg., X, Y, Z
EN 60068-2-6, Vibration	15 G, 10 - 500 Hz, 5h X, Y, Z
IP rating	IP67
Relative humidity	20...80%
Storage temperature	-20...60 °C

Functional Characteristics

Binning	1x1, 2x2, 4x4, 8x8, 16x16
Data storage	64 MB
Decimation	1x1, 2x2, 4x4, 8x8, 16x16
Exposure time	20 µs...20 s
Filter	Cover glass
Image formats	Mono8 Mono10 Mono12 Mono14 Mono16 Mono12Packed Mono12p
MTTF (40 °C)	11.7 a
Trigger mode	Free run Hardware trigger Software trigger

Machine Vision
BVS CA-GX0-0124AG-112C41-XAS2
Order Code: BVS0034



Material

Housing material	Aluminum, Powder coated, Painted
Housing material, surface protection	Powder coated Painted

Mechanical data

Dimension	40 x 40 x 68.7 mm
Lens mount	C-Mount
Weight	140 g

Output/Interface


Digital inputs	4x PNP galvanically isolated
Digital outputs	4x PNP galvanically isolated
Interface	Gigabit Ethernet, POE

Remarks

Not included in the scope of delivery: camera lens, filter, light, connection cable – see www.balluff.com
 For more information about MTTF and B10d see MTTF / B10d Certificate


Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



1) View towards connector
 2) Male 12-pin/ Function

- 2) Power-I/O
- 1 ___ PWR_IN
 - 2 ___ GND
 - 3 ___ DigOut3
 - 4 ___ Opto DigIn0
 - 5 ___ DigOut2
 - 6 ___ DigOut0
 - 7 ___ Opto DigIn_GND
 - 8 ___ Opto DigIn2
 - 9 ___ Opto DigIn3
 - 10 ___ DigOut_PWR_IN
 - 11 ___ Opto DigIn1
 - 12 ___ DigOut1



1) View towards connector
 2) Socket 8-pin/ Function

- 2) GigE LAN
- 1 ___ BI_DA+
 - 2 ___ BI_DA-
 - 3 ___ BI_DB+
 - 4 ___ BI_DB-
 - 5 ___ BI_DD+
 - 6 ___ BI_DD-
 - 7 ___ BI_DC-
 - 8 ___ BI_DC+