

M320TF-MR

32" 4K Chassis Marine Display



KEY FEATURES

- 32" 4K Chassis Marine Display (3840 x 2160) native resolution
- Capacitive touch keys for quick function access and display control
- Thin and Compact Design with impact resistant screen
- AR glass, PCAP touch optional Display
- Fanless cooling design
- VESA Mount



SPECIFICATIONS

| Display | | | |
|----------------------------|---|------------------------------|---|
| Resolution | 3840x2160 | Size | 32 inches |
| Contrast Ratio | 1000:1 | Panel Brightness | 350 nits 700 nits(Optional) |
| Display Color | 1.07B Colors | View Angles | 89,89,89,89 |
| Active Area | 708.48 x 398.52 mm | Touch / Glass | AR Glass Projected Capacitive Multi Touch Screen (Optional) |
| Certification | | | |
| Certification | CE, FCC | | |
| Environment | | | |
| Operating Humidity | 10% to 95% RH | Operating Temperature | -15~55°C |
| Storage Temperature | -20°C~60°C | | |
| IO Ports | | | |
| USB Port | 1 x USB for Touch Screen (Optional) | Serial Port | 1 x RS232 for Remote Control (Optional) |
| Video | 1 x VGA 1 x DVI 1 x Display Port 1.2 1 x HDMI 1.4 (Optional) 1 x HDMI 2.0 (Optional) | Audio | 1 x Audio Line In (Optional) |
| Mechanical | | | |
| Dimension | 777.58 x 477.62 x 48 mm | Mounting | VESA Mount |
| Enclosure | Metal | Cooling System | Fanless Design |
| Accessory | | | |
| Accessory | User Manual(Hardcopy) VESA Mounting Screws (M4 x10 /M4 x 12) Power Cord 1.8M AC Adaptor Power Convert Cable VGA Cable 1.8M(Male to Male) Dual Link DVI Cable 1.8M (Male to Male) COM Cable 1.8M (Male to Female) | Optional Accessory | USB cable for Touch (Optional) |
| Power | | | |

Power Rating

9~36V DC in

DIMENSIONS

UNIT:MM

