

R15L600-MRA3FP

15" ECDIS Marine Display



KEY FEATURES

- 15" 1024 x 768 resolution with projective capacitive multi-touch screen
- Edge-to-edge narrow bezel design and fanless cooling system
- Color calibrated for ECDIS compliance (Optional)
- Capacitive touch keys for quick function access and display control (Support DAY, DUSK, and NIGHT mode switching)
- Meet the requirements of industrial marine standards, including IEC60945 4th Edition, DNVGL-CG-0339, IACS E10



SPECIFICATIONS

Display	
Resolution	1024x768
Contrast Ratio	2500:1
Display Color	16.7M Colors
Optional Function	Option: AR Glass
Size	15.0 inches
Panel Brightness	500 nits
View Angles	88,88,88,88
Touch / Glass	Projected Capacitive Multi Touch Screen Protection Glass (Optional)
Environment	
Operating Humidity	5% to 95%
Operating Temperature	-15~55°C
Shock	15G, 11ms duration
Vibration	0.7g@DNVGL CG-0339 (Class A)
IP rating	IP66 (Front Side)
Certification	
Certification	DNVGL-CG-0339, IEC60945 4th, IACS E10, CE, FCC
IO Ports	
USB Port	1 x USB Type A
Serial Port	1 x RS232 for remote control
Video	1 x VGA 1 x DVI-D 1 x HDMI 1.4
Front Control	Power Brightness+ Brightness- OSD/ Enter ECDIS Key/ ESC
Indicator	Day Mode Dusk Mode Night Mode
Mechanical	
Dimension	363 x 282.91 x 67.5 mm
Mounting	VESA Mount/ Panel Mount
Enclosure	Anodized Aluminum Bezel
Cooling System	Fanless Design
Power	
Power Rating	24V DC-in with Isolation (Approval by Certificate) 9~36V DC Input Acceptable
Accessory	
Accessory	User Manual Quick Start Guide (Hardcopy) M4 x 12 Black Screw Bolts
Optional Accessory	1 x USB cable

AC to DC Adapter
 Power Cord
 3 Pin Terminal Block
 1 x VGA cable
 1 x DVI cable
 1 x HDMI cable
 1 x RS232 cable

DIMENSIONS

UNIT:MM

