

# W26L100-MRA1FP

## 26" ECDIS Marine Display



### KEY FEATURES

- 26" 1920 x 1200 resolution with projective capacitive multi-touch screen
- Edge-to-edge narrow bezel design and fanless cooling system
- Color calibrated for ECDIS compliance (Optional)
- Capacitive touch keys for quick function access and display control (Support ECDIS DAY, DUSK, and NIGHT mode switching)
- Meet the requirements of industrial marine standards, including IEC60945 4th Edition, DNVGL-CG-0339, IACS E10



### SPECIFICATIONS

Display			
<b>Resolution</b>	1920x1200	<b>Size</b>	26.0 inches
<b>Contrast Ratio</b>	1500:1	<b>Panel Brightness</b>	350 nits
<b>Display Color</b>	16.7M Colors	<b>View Angles</b>	88,88,88,88
<b>Touch / Glass</b>	Projected Capacitive Multi Touch Screen AR Glass (Optional)		
Environment			
<b>Operating Humidity</b>	5% to 95%	<b>Operating Temperature</b>	-15~55°C
<b>Shock</b>	15G, 11ms duration	<b>Vibration</b>	0.7g@DNVGL CG-0339 (Class A)
<b>IP rating</b>	IP66 (Front Side)		
Certification			
<b>Certification</b>	DNVGL-CG-0339, IEC60945 4th, IACS E10, CE, FCC		
IO Ports			
<b>USB Port</b>	1 x USB Type A	<b>Serial Port</b>	1 x RS232 for remote control
<b>Video</b>	1 x VGA 1 x DVI-D 1 x HDMI 1.4	<b>Front Control</b>	Power Brightness+ Brightness- OSD/ Enter ECDIS Key/ ESC
<b>Indicator</b>	Day Mode Dusk Mode Night Mode		
Mechanical			
<b>Dimension</b>	621 x 432.4 x 85.5 mm	<b>Mounting</b>	VESA Mount/ Panel Mount
<b>Enclosure</b>	Anodized Aluminum Bezel	<b>Cooling System</b>	Fanless Design
Power			
<b>Power Rating</b>	24V DC-in with Isolation (Approval by Certificate) 9~36V DC Input Acceptable		
Accessory			
<b>Accessory</b>	User Manual Quick Start Guide (Hardcopy) M4 x 12 Black Screw Bolts	<b>Optional Accessory</b>	1 x USB cable

AC to DC Adapter  
 Power Cord  
 3 Pin Terminal Block  
 1 x VGA cable  
 1 x DVI cable  
 1 x HDMI cable  
 1 x RS232 cable

**DIMENSIONS** UNIT:MM

