

Storage SuperServer SSG-640P-E1CR36L



More details here

Key Applications


Enterprise Server, iSCSI SAN, HPC, Data Center, Database Processing & Storage, Corporate Database, Density Optimized Storage Building Block,

Key Features

- Dual socket 3rd Gen Intel® Xeon® Scalable processors, up to 72 Cores Per Node;
- 16 ECC DDR4-3200: LRDIMM/RDIMM + 2 Intel® Optane™ Persistent Memory Dedicated Slots;
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN per node; 2x 10Gbe;
- 36 3.5"/2.5" Hot-swap SAS3/SATA3 drives (4 Hybrid NVMe), 2x Rear SATA Slots, 1x SATA/NVMe M.2 (form factor: 2280 and 22110);
- 7x 8cm hot-swap counter-rotate redundant PWM cooling fans;
- 1600W Redundant Power Supplies Titanium Level (96%);
- HBA Controller support via Broadcom® 3808;



Form Factor	4U Rackmount Enclosure: (17.2" x 7" x 27.5") Package: (27" x 15" x 39")
Processor	3rd Gen Intel® Xeon® Scalable processors Dual Socket LGA-4189 (Socket P+) supported TDP up to 270W; 3 UPI
System Memory	16 DIMM slots Up to 18TB Intel® DCPMM, DDR4-2666MHz Up to 4TB ECC RDIMM/LRDIMM, DDR4-3200MHz
Drive Bays	36x 3.5" hot-swap SATA3/SAS3 drive bays (4x 3.5" NVMe hybrid) 1 M.2 NVMe
Expansion Slots	3 PCIe 4.0 x16 LP slot(s) 1 PCIe 4.0 x8 LP slot(s) Note: PCIe slot 1/2 is occupied by the JBOD Expansion/Storage Controller
On-Board Devices	Chipset: Intel® C621A Network Connectivity: 2x 10GbE BaseT with Intel® X550 IPMI: Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
Input / Output	LAN: 1 RJ45 Dedicated IPMI LAN port USB: 4 USB 3.0 port(s) (4 Rear_USB) Video: 1 VGA port(s) Serial Port: 1 COM Port(s) (1 rear) DOM: 2 SuperDOM (Disk on Module) port



System Cooling	7x 8cm heavy duty fan(s)
Power Supply	1U 800/1600W Single Output Power Supply Titanium Level Dimension (W x H x L): 76.5 x 40 x 360 mm Output Type: 27 Pairs Gold Finger Connector
System BIOS	BIOS Type: AMI 128MB SPI Flash EEPROM
Management	SuperDoctor® 5; Watch Dog; NMI; SUM; IPMI 2.0
PC Health Monitoring	CPU: Monitors for CPU Cores, Chipset Voltages, Memory 4+1 Phase-switching voltage regulator FAN: Fans with tachometer monitoring Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Height: 7" Width: 17.2" Depth: 27.5" Gross Weight: 102.5 lbs (46.4 kg) Net Weight: 65.5 lbs (29.7 kg) Packaging: 15" x 27" x 39" Available Color: Silver
Operating Environment	ROHS: RoHS Compliant Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (Non-Condensing) Non-operating Relative Humidity: 5% to 95% (Non-Condensing)
Motherboard	Super X12DPI-NT6
Chassis	CSE-847BTS-R1K68LPBP4